DROP TESTER

Drop Tester for Packaged Freight

DT-300

DT-300 can aid in providing basic test for package specifications including cushioned package design, selection in packaging materials, fragility of packaged contents, standard test of packaged freights (surfaces only), etc. It can be performed efficiently with a high level of accuracy.

Features

- Free drop in precise posture
- Controlled drop height
- Anti-rebound drop table
- Safe operating conditions

Compliance Standard

- JIS Z 0200
- JIS Z 0202
- ISO 2248

Specification

•	
Model	DT-300
Specimen max size (mm)	W1600 × D1200 × H1500
Specimen max weight (kg)	300
Drop height range (mm)	50 ~ 1000
Drop attitude	Digital setup by a controller
Drop height setting	Digital setup by a controller
Brake of lifting table	Shock absorber and Counter-pressure brake
Size (mm)	W1700 × D1800 × H2600
Capacity (kg)	about 3600
Power supply	AC200V, 3 phases, 7A
Air pressure (MPa)	0.7 or more



SHINYEI TECHNOLOGY CO., LTD.

Tsukuba Office B47-11, Katoridai, Tsukuba, Ibaraki, 300-2657, JAPAN Tel: +81-29-848-3571 FAX: +81-29-848-3572

International Sales Office

Shinyei BLDG. 5F, 77-1 Kyomachi, Chuo-ku, Kobe 651-0178, JAPAN Tel: +81-78-392-6903 FAX: +81-78-332-1619



DT-300 series