

DROP TESTER

DT-80M

Standard Drop Tester for Packaged Freight

DT-80M

Drop Tester, DT-80M, is a standard model that is specialized for drop testing of packaged freight. Test specimens up to 80kg is dropped with high accuracy via a high speed rotational table that is operated from a drop height ranging from 20cm to 180cm automatically without air compressor. Now everyone can conduct drop tests based on compliance standards.

Features

- Standard model with easy functions
- Specialized for packaged freight
- High Repeatability
- Easy to use with automatic operation
- Easy Maintenance for Long Term Usage

Compliance Standard

- ISO 2248 , JIS Z 0202, JIS C 60068-2-31

Option for DT-80M

- Support Jig for corner/edge drop



Specification


Model	DT-80M
Specimen max weight (kg)*	80
Specimen max size (mm)	W900 × D575 × H900 (when flat drop)
Drop height range (mm) *	200 ~ 1800
Operation with drop test	High-speed rotational motion by spring
Capacity (kg)	320
Size (mm)	W920 × D1480 × H2583
Power supply**	AC200V, 3 phases, 5A

Actual article may be different from pictures.

*Customizable options. Please approach your local dealers for further information.

** Localized Power supply available on demand.

The desired falling posture can be set when using a jig (optional).



 **SHINYEI** www.shinyei-tm.com

SHINYEI TECHNOLOGY CO., LTD.

Tsukuba Office B47-11, Katoridai, Tsukuba, Ibaraki, 300-2657, JAPAN

Tel: +81-29-848-3571 FAX: +81-29-848-3572

International Sales Office

Shinyei BLDG. 5F, 77-1 Kyomachi, Chuo-ku, Kobe 651-0178, JAPAN

Tel: +81-78-392-6903 FAX: +81-78-332-1619

Specifications and information listed in this catalog are subject to change without notice.

June 2018